

# POWER<sup>®</sup> pack 6400 universal valve packing

Product name:	<b>POWER<sup>®</sup> pack 6400</b>	Product specification No.:	<b>D – 0043-0-EN</b>	Date:	15. 08. 2013
		Revision Date:		Page:	1 / 1



**Yarn:** braided in round cross sections from 100% pure, unsintered PTFE-tapes. In order to achieve even better impermeability for fluids and gases wrapped with a layer of pure PTFE-tapes. Extremely pliable and durable, excellent chemical and thermal resistance. exceptionally low coefficient of friction. BAM approval.

**Application:** valve packing, can be used as a static seal in many different areas too. Suited for the chemical industry

**Technical data:**

 rotating
  reciprocating
  static

P [bar]	-	-	100
t [°C]	-100 to 280		
pH	0 ÷ 14		
v [m/s]	-		
density	1,6 g/cm <sup>3</sup>		

**Pokorny industries s.r.o.**

Trnkova 115, 628 00 Brno  
 Czech Republic  
 telefon: +420 532 196 711  
 info@pokornyindustries.com



All technical data and recommendations given are based on our experiences. However, we do not undertake any liability whatsoever. All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data and parameters directly on site. The stated parameters are approximate and may be mutually influenced if occurring together. Please contact us in case of difficult or special applications.

**pokornyindustries.com**

